



Output Monitor System

The Perfect Interface OMS (Output Monitor System) was designed to let the car audio enthusiast monitor the outputs of up to four channels of amplification. By using multiple units, more channels can be monitored. Order P.I. part number CA01.

FEATURES:

- 10 LED segments in each meter, the lowest seven are green, the highest three are red
- 1/2 ISO Din Faceplate
- Programmable Dot/Bar Display
- Individual Meter Adjustment
- Smoked Plexi-glass Faceplate
- Compatible with most amps, including all Rockford amps

APPLICATIONS

Single Amp - Outputs can be designated as meter 1 & 2 for left and 3 & 4 for right, or any desired combination.

Multi-Amp Systems - meter 1 left low; meter 2 left high; meter 3 right low; meter 4 right high or any combination an installer can dream up. Monitor multiple channels and/or multiple frequency ranges.

Meter Adjustments - made simply by using a jeweler's screwdriver to adjust individual meters. By moving a jumper, the display can be changed from Dot to a Bar read out.

Installation - made easy by using a standard 1/2 ISO Din faceplate and using chassis mounted screws from any custom installs. Easy to fit - only 1" deep.

SPECIFICATIONS

Dimensions:

1.1" H x 7.1" W x 1.0" D

Displays:

Green and Red LED

Weight:

1.4 lbs.

WARRANTY

1 year parts and labor, subject to verification of the defect. Warranty does not cover improper installation or user abuse. Refer to owner's manual for proper installation.

