

Tockford fosqate.

SPEAKER P-WAY LOUD



RFDJ1

Installation & Operation

Installation et fonctionnement Instalación y funcionamiento Einbau und Betrieb Installazione e funzionamento

Serial Number:	
----------------	--

SAFETY



CAUTION: Before installation, turn-off any part of the audio system to prevent damage to the speaker or system components.

PRACTICE SAFE SOUND™

Continuous exposure to sound pressure levels over 100dB may cause permanent hearing loss. High powered sound systems may produce sound pressure levels well over 130dB. Use common sense and practice safe sound.

FEATURES

Horn Loaded Compression Driver

- I"Titanium diaphragm
- Horn loading provides off axis response and midrange vocal clarity
- Overload protection circuitry
- Field replaceable

12" Passive Speaker


- High efficiency, low distortion design
- · High output with minimal power requirements

High Output Enclosure

- Bass reflex design
- Large volume for better low frequency response
- Integrated ergonomically designed handles
- Interlocking corners allow stacking of multiple cabinets
- Dual Input
 - 5-way binding posts
 - I/4" phono jack
- · Heavy gauge steel mesh grille
- Industry standard I-3/8" pole socket

INSTALLATION


5-Way Binding Posts Strip and insert 16AWG (min) and tighten terminals. Observe proper polarity (+) and (-).



I/4" Phone Jack
If your amplifier has
phono outputs, you
can alternatively use
the I/4" phone jack
connector.


Amplifier/Tuner

For stereo amplifier/tuners, you can connect a stereo pair of speakers to the LEFT and RIGHT outputs. Connect the amplifier (+) to the speaker (+) and the amplifier (-) to the speaker (-). For proper stereo imaging, connect the LEFT output to the LEFT speaker and the RIGHT output to the RIGHT speaker.



SPECIFICATIONS

FEATURE	VALUE
SPEAKER CONFIGURATION	.2-Way Passive Loudspeaker
DRIVER DIAMETER	I" Compression Driver / I2" Woofer
POWER HANDLING	I 50 Watts RMS / 300 Watts MAX
IMPEDANCE	4Ω
DESIGN	2nd Order Vented (Ported)
FREQUENCY RESPONSE	33Hz - 22kHz
SENSITIVITY	92dB
ENCLOSURE MATERIAL	18mm (0.71")
STAND RECEPTACLE	
DIMENSIONS	(H) 24.8" x (W) 14.37" x (D) 12.59"
	630mm x 365mm x 320mm
WEIGHT (ea)	41 Lbs. (18.59kg)
WARRANTY	I Year





LIMITED WARRANTY STATEMENT

Rockford Corporation offers a limited warranty on Rockford Fosgate products on the following

Length of Warranty

- Loudspeakers I Year (receipt required).
- Any Factory Refurbished Product 90 days (receipt required)

What is Covered

This warranty applies only to Rockford Fosgate products sold to consumers by Authorized Rockford Fosgate Dealers in the United States of America or its possessions. Product purchased by consumers from an Authorized Rockford Fosgate Dealer in another country are covered only by that country's Distributor and not by Rockford Corporation.

Who is Covered

This warranty covers only the original purchaser of Rockford product purchased from an Authorized Rockford Fosgate Dealer in the United States. In order to receive service, the purchaser must provide Rockford with a copy of the receipt stating the customer name, dealer name, product purchased and date of purchase. Products found to be defective during the warranty period will be repaired or replaced (with a product deemed to be equivalent) at Rockford's discretion.

What is Not Covered

- 1. Damage caused by accident, abuse, improper operations, water, theft, shipping
- 2. Any cost or expense related to the removal or reinstallation of product
- 3. Service performed by anyone other than Rockford or an Authorized Rockford Fosgate Service Center
- 4. Any product which has had the serial number defaced, altered, or removed
- 5. Subsequent damage to other components
- 6. Any product purchased outside the U.S.
- 7. Any product not purchased from an Authorized Rockford Fosgate Dealer

Limit on Implied Warranties

Any implied warranties including warranties of fitness for use and merchantability are limited in duration to the period of the express warranty set forth above. Some states do not allow limitations on the length of an implied warranty, so this limitation may not apply. No person is authorized to assume for Rockford Fosgate any other liability in connection with the sale of the product.

How to Obtain Service

Contact the Authorized Rockford Fosgate Dealer you purchased this product from. If you need further assistance, call I-800-669-9899 for Rockford Customer Service. You must obtain an RA# (Return Authorization number) to return any product to Rockford Fosgate. You are responsible for shipment of product to Rockford.

EU Warranty

This product meets the current EU warranty requirements, see your Authorized dealer for details.



01/2010 E.W.R. 1230-56250-02

Rockford Fosgate

600 South Rockford Drive Tempe, Arizona 8528 I U.S.A. In U.S.A., (480) 967-3565 - Customer Service I-800-669-9899 www.rockfordfosgate.com

© 2010 Rockford Corporation. All rights reserved.

Rockford Fosgate® and the Rockford Fosgate® "Diamond R" are
registered trademarks of Rockford Corporation.

